


2 PAIR 24 AWG INDUSTRIAL ETHERNET CATEGORY 5E CABLE



CONSTRUCTION

Pair Component

Conductor: 24 AWG 19/36 Tin Plated Copper, 0.024 Inch Diameter

Insulation: 0.0095 Inches of High Density Polyethylene, 0.043 Inch Diameter

Pair: 2 Insulated Conductors Twisted Together, Lay Lengths Varied Between Pairs to Minimize Crosstalk

Final Assembly

Core: 2 Pairs (#1-2) Cabled Together

Inner Jacket: 0.016 Inches of Thermoplastic Elastomer, Color – Natural

Outer Jacket: 0.040 Inches of Thermoplastic Elastomer, Color – Teal Green

Diameter: 0.255 Inches Nominal

Print Legend (Black Ink): "MADISON CABLE 2PR/24 AWG Industrial Ethernet Category 5e 10151721 RoHS COMPLIANT {Date Code}¹"

¹ Date Code is a 4-digit code with the first two digits identifying the calendar week and the last two identifying the calendar year of manufacturing. Example – 0206 for cable manufactured in the second week of January 2006.

COLOR CODE

Pair #	Conductor #1	Conductor #2
1	White/Blue	Blue
2	White/Orange	Orange

ELECTRICAL CHARACTERISTICS

Frequency (MHz)	Attenuation ² dB/100m Nom.	NEXT ³ (dB/Min.)	PSNEXT ⁴ (dB/Min.)	ACR ⁵ (dB/M63.3in)
0.772	2.7	67.0	64.0	65.2
1	3.0	65.3	62.3	63.3
4	6.2	56.3	53.3	52.2
8	8.7	51.8	48.8	46.0
10	9.8	50.3	47.3	43.8
16	12.3	47.2	44.2	39.0
20	14.0	45.8	42.8	36.5
25	15.6	44.3	41.3	33.9
31.25	17.6	42.9	39.9	31.2
62.5	25.5	38.4	35.4	21.4
100	33.0	35.6	32.3	13.3

² Values shown are examples. Attenuation at any frequency between 0.772 and 100 MHz is $1.5(1.967\sqrt{f}+0.023+0.050/\sqrt{f})$ dB/100 meter Maximum, where f is frequency in MHz and measurement is on a length ≥ 100 meters.

³ Values shown are examples. NEXT at any frequency between 0.772 and 100 MHz is $35.3 - 15 \text{Log}_{10}(f/100)$ dB Minimum, where f is frequency in MHz and measurement is on a length ≥ 100 meters.

⁴ Values shown are examples. Power Sum NEXT at any frequency between 0.772 and 100 MHz is $32.3 - 15 \text{Log}_{10}(f/100)$ dB Minimum, where f is frequency in MHz and measurement is on a length ≥ 100 meters. Power Sum Crosstalk is defined as total energy that a pair receives when all other pairs are energized.

⁵ Attenuation Crosstalk Ratio. The difference between attenuation and crosstalk measured in dB at given frequency.

Frequency (MHz)	ELFEXT ⁴ (dB/Min.)	PSELFEXT ⁷ (dB/Min.)	RL ⁸ (dB/Min.)
1	63.8	60.8	20.0
4	51.8	48.8	23.0
8	45.7	42.7	24.5
10	43.8	40.8	25.0
16	39.7	36.7	25.0
20	37.8	34.8	25.0
25	35.8	32.8	24.2
31.25	33.9	30.9	23.3
62.5	27.9	24.9	20.7
100	23.8	20.8	19.0

⁶ Values shown are examples. ELFEXT at any frequency between 1 and 100 MHz is $23.8 - 20 \text{Log}_{10}(f/100)$ dB Minimum, where f is frequency in MHz and measurement is on a length ≥ 100 meters.

⁷ Values shown are examples. Power Sum ELFEXT at any frequency between 1 and 100 MHz is $20.8 - 20 \text{Log}_{10}(f/100)$ dB Minimum, where f is frequency in MHz and measurement is on a length ≥ 100 meters.

⁸ Values shown from 1-100 MHz are examples. Return Loss at any frequency between 1 and 10 MHz is $20 + 5 \text{Log}_{10}(f)$ dB Minimum, between 10 and 20 MHz is 25 Minimum, and between 20 and 100 MHz is $25 - 7 \text{Log}_{10}(f/20)$ dB Minimum, where f is frequency in MHz and measurement is on a length ≥ 100 meters.

REVISION HISTORY

1	11/06/08	DC	Initial Release
2	11/12/08	DC	Revised to 24 AWG, et. al.
3	11/21/08	DC	Revised print legend, removed Separator & UL
4	01/20/09	DC	Revised Ins wall/OD, overall diameter, et. al.

125 Goddard Memorial Drive • Worcester, MA 01603 USA
 Tel: (508) 752-2884 Toll-Free: (877) MADISON Fax: (508) 752-4230

Spec Number: 101-8182
Part Number: 04QFILF001

Customer:	Prepared By: D.M. Card		Page
Customer #:	Reviewed By: K. Arsenault	M. Dupuis	1 of 2

Users should evaluate the suitability of this product for their application. Contact factory for latest revision of specification. Tyco Electronics reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to the Buyer.

2 PAIR 24 AWG INDUSTRIAL ETHERNET CATEGORY 5E CABLE

Impedance⁹: 100 ± 15 Ohms
Pair-to-Ground Capacitance Unbalance: 330 pF/100 m Maximum @ 1 kHz
Velocity of Propagation: 67% Nominal
Time Delay Skew: 45 ns/100 m Maximum from 1 – 100 MHz
Conductor DC Resistance: 24.0 Ohms/1000 ft Nominal @ 20°C
Conductor DC Resistance Unbalance: 5% Maximum

⁹ An Impedance-Like Function Fit to Data By Least Square Method.

MECHANICAL CHARACTERISTICS

Flex Life: 2 Million cycles Minimum. Tested on a C-track machine at @ 1 ½ inch minimum bend radius.

SAFETY CERTIFICATION

RoHS Compliance: In Accordance to European Directive 2002/95/EC, Issue 13.2.2003




 125 Goddard Memorial Drive • Worcester, MA 01603 USA
 Tel: (508) 752-2884 Toll-Free: (877) MADISON Fax: (508) 752-4230

REVISION HISTORY

1	11/06/08	DC	Initial Release
2	11/12/08	DC	Revised to 24 AWG, et. al.
3	11/21/08	DC	Revised print legend, removed Separator & UL
4	01/20/09	DC	Revised Ins wall/OD, overall diameter, et. al.

Spec Number:	101-8182			
Part Number:	04QFILF001			
Customer:		Prepared By:	D.M. Card	Page
Customer #:		Reviewed By:	K. Arsenault M. Dupuis	2 of 2

Users should evaluate the suitability of this product for their application. Contact factory for latest revision of specification. Tyco Electronics reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to the Buyer.