



MATERIAL & FINISH

SHELL

Zinc plated .Tin plated or nickel plated steel

CONTACT (Stamp)

Brass
Gold plated over nickel

Position	A± 0.1	B± 0.1	C± 0.1	D± 0.1	E± 0.1	F± 0.1
09M	16.92	24.99	30.81	1.0	19.28	5.97
15M	25.25	33.32	39.14	1.0	27.51	5.97
19M	30.75	38.94	44.94	1.0	32.86	5.84
23M	35.92	44.28	50.56	1.0	38.38	5.84
25M	38.96	47.04	53.04	1.0	41.43	5.84
37M	55.42	63.50	69.32	1.0	57.71	5.84
50M	52.81	61.12	66.93	1.0	55.32	5.84

ORDER INFORMATION

Contact No.	Contact Type	Mounting Option	Accessories	Shell Plating	Contact Plating	Others
C0540 - 09	M	A	A	A	G	B
09 15 19 23 25 37 50	M: Male	A: Through Hole	A: Non Accessories	A: Tin+Dimple B: Nickel+Dimple Z: Zinc(Chromatic)	S: Selective Gold G: Gold Flash A: Gold 5u" B: Gold 10u" C: Gold 15u" D: Gold 30u"	B: Black Insulator W: White Insulator L: Blue Insulator G: Grey Insulator

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

UNIT

SCALE

PART NAME

MM

2:1

D-Sub Solder Type Male

APPD.

CKD.

TOLERANCE

PART NO.

REV.

制表日:2002/12/04

DRAWING.

APPROVED

± 0.3

C0540-XXMAAXXX

A

kevin