



PCB LAYOUT

SPECIFICATION

Electric
 Current Rating: 5 Amp
 Dielectric Strength: 1000V/ Minute.
 Insulator Resistance: 1000M ohm Min.
 At 500V DC
 Temperature: -55°C ~+105°C

Material

Stell: Zinc Plated Or Tin plated
 Pin Contact: Brass, Gold Plated Over Nickel
 Insulator: PBT&Glass-Fiber Reinforced
 , UL94V-0

POLES	A	B	C	D
9M	16.92	24.99	30.81	19.28
15M	25.25	33.32	39.14	27.51
25M	38.96	47.04	53.04	41.30
37M	55.42	63.50	69.32	57.71
50M	52.86	61.11	66.92	55.30

ORDER INFORMATION

Contact No.	Contact Type	Mounting Option	Accessories	Shell Plating	Contact Plating	Others
C0541- 09	M	A	A	A	S	W
09 15 25 37 50	M: Male	A: Through Hole	A: Non Accessories	A: Tin+Dimple B: Nickel+Dimple Z: Zinc(Chromate)	S: Selective Gold G: Gold Flash A: Gold 6u" B: Gold 10u" C: Gold 15u" D: Gold 30u"	B: Black Insulator W: White Insulator L: Blue Insulator G: Grey Insulator

玄茂科技股份有限公司
 HSUAN MAO TECHNOLOGY CO., LTD.

UNIT

SCALE

PART NAME

MM

2:1

D-SUB P.C.B. STRAIGHT (MALE)

APPD.

CKD.

TOLERANCE

PART NO.

REV.

制表日: 2000/06/07

DRAWING.

APPROVED

± 0.5

C0541-XXMAAXXX

A

Jane