



SPECIFICATION
 Electric
 Current Rating: 5Amp
 Insulator Resistance: 1000M ohm Min.
 (At 500V DC)
 Dielectric Strength: 1000V For One Minute
 Temperature : -55 ° C ~+105 ° C

MATERIAL&FINISH
 Shell: Insulator Glass Filled Nylon
 Stell: Zinc Plated Or Tin Plated
 Pin Contact: Brass, Gold Plated Over Nickel

Shell Size	A	B	C	D
9F	16.33	24.99	30.81	19.28
15F	24.66	33.32	39.14	27.51
25F	38.38	47.04	53.04	41.30
37F	55.84	63.50	69.32	57.71

ORDER INFORMATION

C0542-

09
15
25
37
50

F: Female A: Through Hole

A: Non Accessories

T: Tin
N: Nickel
Z: Zinc(Chromatic)

B: Black Fill It With '0'

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

制表日: 2002/12/04	DRAWING.	APPROVED
	kevin	

UNIT		SCALE	PART NAME	
MM		2:1	D-SUB CRIMPING HOUSING (FEMALE)	
APPD.	CKD.	TOLERANCE	PART NO.	REV.
		± 0.3	C0542-XXFAAXX0	A