



MATERIAL & FINISH

SHELL

Tin plated zinc plated or nickel plated steel

CONTACT (stamp)

Brass

Gold plated over nickel

Position	A± 0.1	B± 0.1	C± 0.1	D± 0.1	E± 0.1	F± 0.1
15M	30.8	16.9	0.25	2.29	24.99	19.3
26M	39.1	25.3	0.51	2.29	33.32	27.5
44M	53.0	39.0	0.51	2.29	47.04	41.3
62M	69.3	55.4	0.58	2.41	63.50	57.7

ORDER INFORMATION

Contact No.	Contact Type	Mounting Option	Accessories	Shell Plating	Contact Plating	Others
C0560 - <input type="text" value="15"/>	<input type="text" value="M"/>	<input type="text" value="A"/>	<input type="text" value="A"/>	<input type="text" value="A"/>	<input type="text" value="G"/>	<input type="text" value="B"/>
15 26 44 62 78	M: Male	A: Throught Hole	A: Non Accessories	A: Tin+Dimple B: Nickel+Dimple Z: Zinc(Chromatic)	S: Selective Gold G: Gold Flash A: Gold 5u" B: Gold 10u" C: Gold 15u" D: Gold 30u"	B: Black Insulator W: White Insulator L: Blue Insulator G: Grey Insulator

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

UNIT

SCALE

PART NAME

MM

2 : 1

H.D. D-Sub Solder Type Male

APPD.

CKD.

TOLERANCE

PART NO.

REV.

制表日: 2002/12/04

DRAWING.

APPROVED

kevin

± 0.3

C0560-XXMAAXXX

A