



SPECIFICATION:
 Contact Resistance: 30m ohm ma:
 30m ohm max.
 Insulator Resistance:
 1000m ohm min. at DC 500V
 Current Rating:
 1 AMP
 Dielectric Withstanding Voltage:
 AC 500V For 1 minute
 Operating Temperature:
 -55°C ~ +105°C
 Contact Material:
 Brass
 Insulator Material:
 PBT & 30% Glass Fiber UL 94V-0

WITH EAR

Position	A	B	C	D
10	10.16	18.00	37.20	23.00
14	15.24	23.08	42.28	28.08
16	17.78	25.62	44.82	30.62
20	22.86	30.70	49.90	35.70
24	27.94	35.78	54.98	40.78
26	30.48	38.32	57.52	43.32
30	35.56	43.40	62.60	48.40
34	40.64	48.48	67.68	53.48
40	48.26	56.10	75.30	61.10
50	60.96	68.80	88.00	73.80
60	73.66	81.50	100.70	86.50
64	78.74	86.58	105.78	91.58

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

UNIT		SCALE	PART NAME	
MM		2:1	2.54mm Box Header W/Ear IDC Type	
APPD.	CKD.	TOLERANCE	PART NO.	REV.
		±0.2	C3501-XXX YXG00	A

制表日: 2002/12/04

DRAWING. APPROVED
Kevin