



SPECIFICATIONS

Current Rating: 1Amps
 Insulator resistance: 1000 Megohms min.
 Voltage: AC 500V For One minute
 Operating Temperature: -55°C~+105°C
 Contact Material: Bronze
 Contact Plating: Gold Flash
 Standard: PBT+30%Glass-Fiber(UL-94-V0)
 Contact Resistance: 100mv min. At DC 500V

| No of Contacts | Dimensions | | |
|----------------|------------|-------|-------|
| | A | B | C |
| 10pin | 20.3 | 18.1 | 10.16 |
| 14pin | 25.38 | 23.18 | 15.24 |
| 16pin | 27.92 | 25.72 | 17.78 |
| 20pin | 33.0 | 30.8 | 22.85 |
| 26pin | 40.62 | 38.42 | 30.48 |
| 34pin | 50.8 | 48.58 | 40.64 |
| 40pin | 58.4 | 56.2 | 48.26 |
| 50pin | 71.1 | 68.9 | 60.96 |

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

UNIT

SCALE

PART NAME

MM

2:1

2.54 X 2.54mm Box Header
 Straight /Black Insulator

APPD.

CKD.

TOLERANCE

PART NO.

REV.

制表日:2002/12/04

DRAWING.

APPROVED

±0.2

C3510-XXSPXXX0

A

Jane