



P/N	WIRE OPTION
H8254-XXPDTW00	#22
H8254-XXPETW00	#24
H8254-XXPFTW00	#26
H8254-XXPGTW00	#28

SPECIFICATION

- .Current rating : 2A,AC/DC
- .Voltage rating : 250V AC/DC
- .Applicable wire : AWG#24-#18
- .Material : Nylon UL 94V-2
- .Contact : Brass

Dimensional information

Circuits	Dim A	Dim B	Circuits	Dim A	Dim B
2	2.54	5.08	16	38.10	40.64
3	5.08	7.62	17	40.64	43.18
4	7.62	10.16	18	43.18	45.72
5	10.16	12.70	19	45.72	48.26
6	12.70	15.24	20	48.26	50.80
7	15.24	17.78	21	50.80	53.34
8	17.78	20.32	22	53.34	55.88
9	20.32	22.86	23	55.88	58.42
10	22.86	25.40	24	58.42	60.96
11	25.40	27.94	25	60.96	63.50
12	27.94	30.48	26	63.50	66.04
13	30.48	33.02	27	66.04	68.58
14	33.02	35.56	28	68.58	71.12
15	35.56	38.10			

玄茂科技股份有限公司

HSUAN MAO TECHNOLOGY CO.,LTD.

製表日:2000/01/15

DWG.
TINA

APPROVED
SHELLEY

UNIT
MM

SCALE
5 : 1

PART NAME

P:2.54 IDC CONNECTOR

APPD.

CKD.

TOLERANCE

± 0.5

PART NO.

H8254-XXPXTW00

REV.

A