



Quick Reference Guide F Series Switches

The F Series switches offer high performance industrial toggles, rockers, and paddles with high current and high voltage rating in a small case. The F Series encompasses many circuit configurations ranging from single pole through four poles, in two and three positions with a choice of momentary or maintained circuits. This toggle series is UL, CSA recognized for 6A at 250 VAC, 6A at 125VAC with silver contacts and 0.4 VA max. at 20 V AC/DC with optional gold plated contacts, typically used for low energy switching. Electrical life is rated from 25,000 to 50,000 cycles at full load. Other electrical parameters include contact resistance of 10 milliohms max., insulation resistance of 1,000 megohms and actuation force of 19.6 N max.

All F Series switches are panel mounted with 6.0 mm threaded bushing conforming to standard panel cut outs and are constructed of brass with chrome plating. Design engineers are given the option of three toggle styles: standard toggle, locking lever to avoid unwanted switching and long flat toggle.

FEATURES

- Wide choice of toggles, rockers, and paddles
- Wide range of switch functions
- Terminals are gold-flashed to prevent oxidation and for ease of soldering

Applications

These devices are designed to meet requirements of light to medium-duty applications including:

- Industrial
- Instrumentation
- Medical equipment

Typical Performance Characteristics

- Number of Poles** : 1 to 4
- Switch Functions** : ON-ON, ON-(ON), ON-OFF-ON, ON-ON-ON, ON-OFF-(ON), (ON)-OFF-(ON)
- Contact Rating** : 6 A @250 VAC, 6 A @125 VAC,
Gold Contact : 0.4 VA max. 20 V AC/DC
- Electrical Life** : 25,000 to 50,000 cycles
- Mechanical Life** : 50,000 to 100,000 cycles
- Contact Resistance** : Max. 10 mOhm
- Insulation Resistance** : Min. 1,000 MOhm
- Dielectric Strength** : 1,000 VAC for 1 min.
- Actuation Force** : Max. 19.6 N
- Panel Cut-out** : 6.2 mm
- Standards and Specs** : UL, CSA

Material Specifications

- Contacts** : Brass silver alloy finish
- Toggle** : Brass chromium plated
- Terminals** : Brass plate
- Case** : Phenol resin
- Cover** : Steel zinc plated
- Seal** : Rubber seal, insert molded rubber


Other Characteristics

- Contact Timing** : Break before Make
- Right Angle Versions** : No
- Standard Number of Positions** : 2 or 3
- Terminals / Mounting Style** : Leadwire hooking
- Actuator Style** : Standard, long locking; rocker
- Dimensions Case (LxWxH)** : 14.8 x 8 ... 23 x 10.5 mm
- Packaging** : Bulk
- Choice of momentary or maintained circuits**

Environmental Specification

- Operating Temperature** : -20 to +70°C
- Storage Temperature** : -20 to +70°C
- Vibration Resistance** : 1.5 mm 10-55 Hz
- Shock Resistance** : 50 g for 11±1 msec
- Terminal Strength** : 24.5 N

F Series Toggle Switches Product Key



Actuator



Code 0 – Standard Toggle




Code 7 – Long Flat Toggle




Code 5 – Locking Lever

Terminal



Code 9 – Leadwire Hooking Type

Mounting – F Series Toggles



Recommended Hole Layout to Prevent Rotation


GOLD CONTACTS 0.4 VA MAX. AT 20 V AC/DC

| Product Key | Poles | Switch Function | Actuator | Terminal | Contacts | Part Number |
|-------------|---------|-----------------|------------------------|-----------------------|----------|-------------|
| FTD09G04 | 1 pole | ON-ON | Standard Locking Lever | Leadwire Hooking Type | Gold | 3-6437630-4 |
| FTD59G04 | 1 pole | ON-ON | Flat Toggle Standard | Leadwire Hooking Type | Gold | 4-6437630-0 |
| FTD79G04 | 1 pole | ON-ON | Flat Toggle Standard | Leadwire Hooking Type | Gold | 5-6437630-4 |
| FTE09G04 | 1 pole | ON-OFF-ON | Flat Toggle Standard | Leadwire Hooking Type | Gold | 5-6437630-1 |
| FTE79G04 | 1 pole | ON-OFF-ON | Flat Toggle Standard | Leadwire Hooking Type | Gold | 5-6437630-8 |
| FTF09G04 | 1 pole | ON-(ON) | Flat Toggle Standard | Leadwire Hooking Type | Gold | 6-6437630-3 |
| FTG09G04 | 1 pole | (ON)-OFF-(ON) | Flat Toggle Standard | Leadwire Hooking Type | Gold | 3-6437630-8 |
| FTH09G04 | 1 pole | ON-OFF-(ON) | Flat Toggle Standard | Leadwire Hooking Type | Gold | 6-6437630-4 |
| FTN09G04 | 2 poles | ON-ON | Flat Toggle Standard | Leadwire Hooking Type | Gold | 6-6437630-8 |
| FTN59G04 | 2 poles | ON-ON | Flat Toggle Standard | Leadwire Hooking Type | Gold | 6-6437630-1 |
| FTN79G04 | 2 poles | ON-ON | Flat Toggle Standard | Leadwire Hooking Type | Gold | 5-6437630-9 |

SILVER CONTACTS 6A AT 250/125 VAC

| Product Key | Poles | Switch Function | Actuator | Terminal | Contacts | Part Number |
|-------------|---------|-----------------|---------------|-----------------------|----------|-------------|
| F3TD0904 | 3 Poles | ON-ON | Standard | Leadwire Hooking Type | Silver | 2-6437630-8 |
| F4TD0904 | 4 Poles | ON-ON | Standard | Leadwire Hooking Type | Silver | 3-6437630-5 |
| F4TPA0904 | 4 Poles | ON-ON-ON | Standard | Leadwire Hooking Type | Silver | 3-6437630-6 |
| FTD0904 | 1 Pole | ON-ON | Standard | Leadwire Hooking Type | Silver | 2-6437630-0 |
| FTD5904 | 1 Pole | ON-ON | Locking Lever | Leadwire Hooking Type | Silver | 1-6437630-5 |
| FTD7904 | 1 Pole | ON-ON | Flat Toggle | Leadwire Hooking Type | Silver | 5-6437630-3 |
| FTE0904 | 1 Pole | ON-OFF-ON | Standard | Leadwire Hooking Type | Silver | 6-6437630-2 |
| FTF0904 | 1 Pole | ON-(ON) | Standard | Leadwire Hooking Type | Silver | 5-6437630-7 |
| FTG0904 | 1 Pole | (ON)-OFF-(ON) | Standard | Leadwire Hooking Type | Silver | 5-6437630-5 |
| FTH0904 | 1 Pole | ON-OFF-(ON) | Standard | Leadwire Hooking Type | Silver | 4-6437630-8 |
| FTN0904 | 2 Poles | ON-ON | Standard | Leadwire Hooking Type | Silver | 4-6437630-2 |
| FTN5904 | 2 Poles | ON-ON | Locking Lever | Leadwire Hooking Type | Silver | 3-6437630-9 |
| FTN7904 | 2 Poles | ON-ON | Flat Toggle | Leadwire Hooking Type | Silver | 5-6437630-2 |
| FTP0904 | 2 Poles | ON-OFF-ON | Standard | Leadwire Hooking Type | Silver | 4-6437630-6 |
| FTPA0904 | 2 Poles | ON-OFF-ON | Standard | Leadwire Hooking Type | Silver | 4-6437630-5 |
| FTR0904 | 2 Poles | ON-(ON) | Standard | Leadwire Hooking Type | Silver | 4-6437630-4 |
| FTS0904 | 2 Poles | (ON)-OFF-(ON) | Standard | Leadwire Hooking Type | Silver | 4-6437630-3 |
| FTT0904 | 2 Poles | ON-OFF-(ON) | Standard | Leadwire Hooking Type | Silver | 4-6437630-1 |

F Series Rocker Switches Product Key



Actuator




Code 1 – Long Rocker



Code 2 – Small Rocker

Mounting – F Series Rocker



**Panel Cutout
Thickness 1 to 2.5 mm**

| ROCKER | | | | | | | |
|---------------|---------|-----------------|--------------|----------------|-----------------------|----------|-------------|
| Product Key | Poles | Switch Function | Actuator | Actuator Color | Terminal | Contacts | Part Number |
| FLD19black04 | 1 Pole | ON-ON | Long Rocker | Black | Leadwire Hooking Type | Silver | 3-6437630-2 |
| FLD29black04 | 1 Pole | ON-ON | Small Rocker | Black | Leadwire Hooking Type | Silver | 2-6437630-9 |
| FLN19black04 | 2 Poles | ON-ON | Long Rocker | Black | Leadwire Hooking Type | Silver | 3-6437630-7 |
| FLN29red04 | 2 Poles | ON-ON | Long Rocker | Red | Leadwire Hooking Type | Silver | 2-6437630-7 |
| FLN19white04 | 2 Poles | ON-ON | Long Rocker | White | Leadwire Hooking Type | Silver | 2-6437630-6 |
| FLN29black04 | 2 Poles | ON-ON | Small Rocker | Black | Leadwire Hooking Type | Silver | 2-6437630-5 |
| FLN29red04 | 2 Poles | ON-ON | Small Rocker | Red | Leadwire Hooking Type | Silver | 4-6437630-7 |
| FLN29white04 | 2 Poles | ON-ON | Small Rocker | White | Leadwire Hooking Type | Silver | 2-6437630-3 |

| ACCESSORIES | | | |
|--------------------|----------------------|-------|-------------|
| Product Key | Switch Compatibility | Color | Part Number |
| Bezel | FL Series | Black | 9-6437631-0 |
| Bezel | FL Series | Red | 9-6437631-1 |
| Cap04 | F Series Toggles | Black | 9-6437630-0 |

How to Specify in a Switch

Electrical Considerations

Voltage of Applications: _____ Current of Application: _____
Circuitry Configuration: Number of Poles: _____ Number of Throws: _____
Number of Operations anticipated: _____
Agency Approvals or Listings Desired: _____

Mechanical Considerations

Type of Switch (Actuator Type): _____ Toggle _____ Pushbutton _____ Rotary _____ Rocker _____ Other
Switch Function (On/Off/On): _____ On/Off: _____ Momentary: _____
Termination: _____ Thru-Hole (PC) _____ Surface Mount _____ Wire Lug _____ Quick Connect _____ Other
Sealing Contamination Requirements: _____

Product Processing Considerations

Anticipated Soldering Process: _____ Hand _____ Wave _____ SMT _____ Other

FOR MORE INFORMATION

Technical Support

Internet: www.tycoelectronics.com/help
USA: +1 (800) 522-6752
Canada: +1 (905) 470-4425
Mexico & Central America: +52(0) 55-1106-0814
South America: +55 (0) 11-2103-6000
Germany: +49 (0) 6251-133-1999
UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015

Part numbers in this brochure are RoHS Compliant*, unless marked otherwise.

*as defined www.tycoelectronics.com/leadfree

Tyco Electronics Corporation, Berwyn, PA

tycoelectronics.com

© 2010 Tyco Electronics Corporation. All Rights Reserved.

1-1773458-9 CIS LUG FP 3M 08/2010

TE (logo) and Tyco Electronics are trademarks of the Tyco Electronics group of companies and its licensors.

Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

While Tyco Electronics has made every reasonable effort to ensure the accuracy of the information in this catalog, Tyco Electronics does not guarantee that it is error-free, nor does Tyco Electronics make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. Tyco Electronics reserves the right to make any adjustments to the information contained herein at any time without notice. Tyco Electronics expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult Tyco Electronics for the latest dimensions and design specifications.

**Tyco Electronics**
Our commitment. Your advantage.