



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)
 SHELL: STAINLESS STEEL, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 1.8 AMP MAX (ONLY PIN 1,5), OTHER 1 AMP MAX
 DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 50m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -30°C~+80°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	GENERAL TOLERANCE: X ±0.30 Ang. ±3° XX ±0.20 XXX ±0.10	PART NAME 品名 Micro USB AB TYPE FEMALE 5P PIN:SMT TYPE (P.C.B TYPE) WITH LOCATING PEG MATTE TIN SHELL(FOOT:DIP TYPE) BLACK INSULATOR REEL PACKING ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE: 紙張尺寸 A 4	PART NO. 料號 C8359-05ZFDXYBFR
DATE 制表日 2013/09/17	PAGE 張數 1 OF 1	REV. 版次 A	