



■ SPECIFICATIONS

- ◆ Applicable Wire: AWG#28~#22
- ◆ Rated voltage: 250V DC,AC
- ◆ Rated Current: 3A
- ◆ Withstand voltage: 1000V AC/min.
- ◆ Working Temp : -25°C ~ +85°C
- ◆ Insulation resistance: ≥1000 MΩ
- ◆ Contact resistance: ≤30mΩ

■ MATERIAL

- ◆ Housing: Nylon66, UL94-V0

	2x4P	2x5P	2x6P	2x7P	2x8P	2x9P	2x10P	2x11P	2x12P	2x13P	2x14P	2x15P	2x16P	2x17P	2x18P	2x19P	2x20P	2x30P
DIM.A	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.0	22.0	24.0	26.0	28.0	30.0	32.0	34.0	36.0	38.0	58.0
DIM.B	10.9	12.9	14.9	16.9	18.9	20.9	22.9	24.9	26.9	28.9	30.9	32.9	34.9	36.9	38.9	40.9	42.9	62.9
DIM.C	1.4	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
DIM.D	5.0	6.0	8.0	10.0	12.0	14.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0

<p>RoHS Compliant</p>		<p><b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准 Betty</p>		<p>GENERAL TOLERANCE XX ± 0.40 X ± 0.30 X ± 0.25 X* ± 0.2 XX ± 0.15 X* ± 1*</p>	<p>PART NAME 品名 2.0mm HOUSING 2XXXP WHITE COLOR NYLON66 UL94V-0 ROHS</p>
<p>DWG. 製圖 Betty</p>	<p>SCALE 比例 參考</p>	<p>UNIT 單位 M M</p>	<p>PART NO. 料號 H2013-XXPDW000R</p>
<p>DATE 制表日 2013/09/26</p>	<p>PAGE 張數 1 OF 1</p>	<p>REV. 版次 A</p>	