



# FHxx\*1)S24Gy\*2)-0981

e.g. FH15S24G1-0981

- \*1) xx No. of contacts 09, 15, 25 or 37
- \*2) y for performance classes 1, 2 or 3 (contact cycle for G1/G2/G3 = 500/200/50)

xx	A [mm]	B [mm]	C [mm]	*E [mm]	*H [mm]
09	30.8	16.4	25	ø1	ø3
15	39.1	24.7	33.3		
25	53	38.5	47.04		
37	69.3	55.9	63.5		

RoHS compliant

\*PCB hole patterns, øE, øF on supplement AM0023

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
4	2	Snap-in bolt	PCB 1.6mm / Brass	tin plated
3	xx	Signal contact	S24 / Brass	G1/G2/G3
2	1	Shell	Steel	tin plated
1	1	Insulator	PCT (-55°C - +150°C)	natural



Measurement without tolerance occ. to ISO 2768-m

SCALE 2:1

TITLE

NAME / DATE  
DRAWN Mpostulka 03-04-2014  
CHECKED sschref 03-04-2014

D-Sub Miniature Connector



DWG.NO.

FHxxS24Gy-0981

REV.

1

REV.

DATE

CH.-NO.

ORIGINAL: DIN A3-DRAWING AS A FILE

REPLACEMENT FOR:

PAGES 1